AUTOPAGE
VEHICLE SECURITY ALARM SYSTEMS

Better Security Made Affordable

C3 RS-900LCD

2- Way LCD 900Mkz Remote Car starter w/ 6 channel Alarm

C3 RS-900LCD *NEW 900MHz,* Six-Channel Alarm System with Remote Car Starter and Two Way FM/FM Paging LCD Remote Transmitter

STANDARD COMPONENTS:

- ***New* C/3 Compatible for Telematic Cell Phone Interface.**
- 6 Channel Alarm and Remote Car Starter with 5 on-board MICRO relays for parking lights, starter, accessories, ignition 1&2 and one additional relay / socket for starter disable.
- ***New*** On-board Serial Port for **AP Data Link** Data Bus Integration
- Two-way paging receiver and transmitting remote with 3-color LCD screen using FM frequency bands for transmitting and receiving at 900 megahertz. Unit will transmit and receive up to 1 MILE. Unit also includes 24-hour clock with meter minder and temperature indicator and countdown run timer.
- New MANCHESTER CODE encoder.
- NEW STYLE Two-way, window mount SUPER EXTENDED RANGE transceiver antenna module.
- One 5-button extended range FM, standard 900-megahertz SLIDE COVER remote transmitter.
- SIS-11 Super Intelligent Sensor with dual stage shock / glass sensitivity.
- Discrete Temperature Sensor that communicates in-car temperature with LCD remote.
- Window-mount Knock Sensor for driver paging.
- Plug-in super bright mini-BLUE LED and push-type valet/override switch.

TWO-WAY LCD REMOTE OPERATION:

- 5-button configuration with selectable Button Lock to prevent accidental mis-use.
- Uses one AAA type 1.5volt alkaline battery with battery life indicator and power save mode
- 3-color LCD screen displays 29 icons and figures that provide for around-the-clock visual confirmation on vehicle and alarm status. Back lighting for nighttime use. Channels

3,4,5,6 indicators on LCD screen

- Optional Two Car Operation with LCD transmitter only
- Transmits on FM band and receives on FM band.
- 24-hour digital clock with count down timer for parking meter reminder. The clock doubles as a temperature indicator for monitoring in-car temperature. Displays in Fahrenheit or Celsius.
- Multiple audible confirmation tones as well as vibrator mode for paging.

LCD Transmitter Range Check Indicator

ALARM FEATURES:

- Six Channels of outputs (3 dedicated to lock/unlock, trunk and remote start / 3 auxiliary outputs)
- Dedicated function buttons on LCD remote and 4-button standard remote transmitter.
- Code learning / Anti-scan receiver with programmable code hopping.
- Back-up memory system
- Selectable Chirp Confirmation (OEM Style lock only chirp confirmation)
- Comfort Feature with OEM systems having key / remote control power window roll-up
- Dedicated remote panic and car locator
- Passive arming by-pass from the remote
- Parking light flash with dual polarity relay on-board
- Plug-in dual stage SIS-11shock sensor with sensor by-pass from the remote
- Starter disable output with relay and socket included
- Dome light illuminated entry output
- Dual polarity (+/-) door lock outputs with optional driver s door priority two step unlock
- Additional positive and negative inputs
- 500 mA grounded outputs for starter disable and door lock/unlock
- Programmable momentary, latched or timer on 3 auxiliary channels.
- Programmable manual / passive arming with true last door arming with auto re-arm on
- Programmable Single / Double Pulse Unlock (7 new timing adjustments)
- Programmable Parking lights (flash or constant)
- Programmable Pathway Illumination (on / off)
- Programmable voltage sense for delayed dome lights (on / off)
- Programmable horn and siren chirp delete
- Programmable ignition control lock and unlock
- Programmable pulse time for lock and unlock (.9 sec. / 3 sec.)

REMOTE CAR STARTER FEATURES:

- 5 On-Board Relays:

1. Ignition 1
2. Ignition 2
3. Starter
4. Accessory
5. Parking Light

- 3rd Ignition (-) output
- Dedicated Second Start wire
- Dedicated Ground out when running

- GM- Non starter wire timing compatible
- Ground when start (-) output
- New Turbo Timer feature
- 2nd Accessory (-) output
- Selectable one or two push Safety Start
- Programmable gasoline or diesel with 10, 15, or 20 second Wait-to-Start
- Hood pin switch safety input (pin switch included)
- Selectable RPM / Voltage Start
- RPM / Voltage / Hi-Low level check
- Timer control start option
- Sensor control output during start
- Temporary Stop Feature
- Factory Alarm Disarm and Rearm signal output
- Programmable factory keyless door locking before and after start
- Programmable start status output with shock sensor bypass
- 45 second door / dome light bypass after ignition is turned off.
- Programmable Ignition 2 (on / off)
- Programmable 3 hour timer start
- Programmable 1 / 3 hour timer start
- Selectable Run Timer (5/10/20/30 minutes)
- Selectable Gasoline / diesel
- Selectable Diesel warm-up time

NEWS & TECHNOLOGY

2-WAY COMMUNICATION

SECURITY/REMOTE STARTS

Product Registration | Corporate Profile | Privacy Policy | Legal | Sitemap

© 2004 AUTOPAGE, INC. ALL RIGHTS RESERVED